Please amend the Application as follows:

IN THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

- 1. (Original) A method of treating a plastic article comprising:
 - (a) providing a plastic article comprising at least one polymer selected from thermoplastic polymer and thermoset polymer;
 - (b) contacting at least a portion of the surface of said plastic article with a treatment composition comprising,
 - (i) at least one additive selected from UV stabilizers, optical brighteners, mold release agents, antistatic agents, thermal stabilizers, IR absorbers and antimicrobial agents,
 - (ii) water,
 - (iii) at least one carrier represented by the following general formula I,

$$R^{1} - \left(CH_{2}\right)_{n} - \left(CH_{2}\right)_{m} - R^{2}$$

wherein R¹ is a radical selected from the group consisting of linear or branched C₁-C₁₈ alkyl, benzyl, benzoyl and phenyl,

R² is a radical selected from the group consisting of linear or branched C₁-C₁₈ alkyl, benzyl, benzyl, phenyl and H,

n is 2, 3 or 4, and

m is 1 to 35, and

(iv) a diol selected from at least one of linear or branched C₂-C₂₀ aliphatic diols, poly(C₂-C₄ alkylene glycol), cycloaliphatic diols

having from 5 to 8 carbon atoms in the cyclic ring, monocyclic aromatic diols, bisphenols and hydrogenated bisphenols;

- (c) maintaining said portion of said plastic article in contact with said treatment composition for a period of time at least sufficient to form a treated plastic article; and
- (d) removing said treated plastic article from contact with said treatment composition.
- 2. (Original) The method of Claim 1 wherein said treatment composition is maintained at a temperature of 25 to 99°C
- 3. (Original) The method of Claim 1 wherein said plastic article is contacted with said treatment composition by at least one of:
 - (I) dipping at least a portion of the surface of said plastic article into said treatment composition; and
 - (II) applying said treatment composition to at least a portion of the surface of said plastic article.
- 4. (Original) The method of Claim 3 wherein said treatment composition is applied to at least a portion of the surface of said plastic article by at least one of spray application, curtain application and spin application.
- 5. (Original) The method of Claim 1 wherein said plastic article comprises a polymer selected from at least one of (co)polyesters, (co)polycarbonates, polyesterpolycarbonate copolymers, acrylonitrile-butadiene-styrene copolymers, polyamides, polyurethanes, polyalkyl(meth)acrylate and styrene copolymers.
- 6. (Original) The method of Claim 1 wherein R¹ is selected from linear or branched C₁-C₁₈ alkyl, R² is selected from linear or branched C₁-C₁₈ alkyl and H, and n is 2.

PO-8027

- 7. (Original) The method of Claim 6 wherein R¹ is selected from n-butyl, i-butyl and t-butyl, and R² is selected from n-butyl, i-butyl, t-butyl and H.
- 8. (Original) The method of Claim 1 wherein said treatment composition further comprises a surfactant that is different than said carrier, said surfactant being selected from at least one of: anionic surfactants; amphoteric surfactants; and a non-ionic surfactant selected from at least one poly(C_2 - C_4 alkoxylated) C_{14} - C_{18} unsaturated fatty acid.
- 9. (Original) The method of Claim 8 wherein said surfactant is present in an amount of from 1 to 15 percent by weight, based on the total weight of said treatment composition.
- 10. (Original) The method of Claim 1 wherein said diol is a poly(C₂-C₄ alkylene glycol) selected from diethylene glycol, triethylene glycol, tetraethylene glycol, pentaethylene glycol and mixtures thereof.
- 11. (Original) The method of Claim 10 wherein said diol is diethylene glycol.
- 12. (Original) The method of Claim 10 wherein R^1 is selected from linear or branched C_1 - C_{18} alkyl, R^2 is H, n is 2 and m is 1.
- 13. (Original) The method of Claim 12 wherein R¹ is selected from n-butyl, i-butyl and t-butyl.
- 14. (Original) The method of Claim 1 wherein said plastic article comprises at least one of static dyes, photochromic dyes, pigments, crosslinked polymethylmethacrylate microspheres, glass microspheres and metal flakes.

- 15. (Original) The method of Claim 1 wherein said plastic article comprises a thermoplastic polycarbonate selected from at least one of thermoplastic aromatic polycarbonates and thermoplastic aliphatic polycarbonates.
- 16. (Original) The method of Claim 1 wherein said plastic article is a molded article comprising a thermoset polycarbonate.
- 17. (Original) The method of Claim 16 wherein said thermoset polycarbonate is a polymerizate of a polymerizable composition comprising polyol(ally carbonate) monomers.
- 18. (Original) The method of Claim 1 wherein said plastic article is a molded article selected from shaped articles, films and sheets.
- 19. (Original) The method of Claim 18 wherein said molded article is a shaped article selected from optical lenses, ophthalmic lenses, sunshade lenses and glazings.
- 20. (Original) The method of Claim 1 wherein said plastic article is selected from thermoplastic pellets and thermoplastic strands.
 - 21. (Original) The method of Claim 20 further comprising, melting at least one of said treated thermoplastic pellets and said treated thermoplastic strands to form a treated molten thermoplastic composition, and

introducing said treated molten thermoplastic composition into a mold,

thereby forming a treated shaped molded article.

22. (Original) The method of Claim 1 further comprising contacting said treated plastic article with a dye composition comprising at least one dye, thereby forming a treated and dyed plastic article.

23. (Cancelled)

- 24. (Original) The method of Claim 1 further comprising:
- (i) contacting said treatment composition with particulate activated carbon to form a mixture of said treatment composition and particulate activated carbon;
 - (ii) isolating from said mixture a substantially additive-free liquid comprising water, said carrier and said diol; and
 - (iii) optionally adding at least one additive to said substantially additive-free liquid, thereby forming a further treatment composition.
- 25. (Original) The method of Claim 1 further comprising: forming said treatment composition by,
 - (i) preparing a mixture of water, said carrier and said diol,
 - (ii) introducing said additive into a filter, and
- (iii) passing said mixture over said additive and through said filter, thereby forming said treatment composition; and passing continuously said treatment composition through said filter.
- 26. (Original) The method of Claim 1 further comprising, introducing continuously said treatment composition into an immersion tank through a plate having a plurality of perforations.
- 27. (Original) The method of Claim 1 wherein said treatment composition further comprises at least one dye selected from static dyes and photochromic dyes.
- 28. (Original) The method of Claim 1 further comprising contacting at least a portion of the surface of the treated plastic article removed from contact with said treatment composition with a rinse composition comprising water, and optionally at least one of said carrier (iii) and said diol (iv).

PO-8027